



技术参数:

- 材料: 铜合金
- 表面处理: 镀银
- 额定电流: 100A
- 接触电阻: $\leq 0.3m\Omega$
- 线径范围: $35mm^2$
- 最大电缆直径: 14mm
- 剥线长度: 16mm
- 可插拔次数: ≥ 500
- 电缆绞线标准: IEC 60228-5

Technical specification:

- Material: copper alloy
- Surface: hard-silver plated
- Rated current: 100A
- Contact resistance: $\leq 0.3m\Omega$
- Wire gauge: $35mm^2$
- Max. insulation diameter: 14mm
- Stripping length: 16mm
- Mating cycles: ≥ 500
- For stranded fine wire acc. to: IEC 60228-5

REVISION		DATE	
SW	DESCRIPTION	DATE	APPROVED

Tolerance	SIGNATURE	DATE	Units	mm	NINGBO OUKERUI CONNECTOR CO., LTD.	
0~ $\leq 6 \pm 0.03$	DRAW		Size	A4	宁波欧科瑞连接器有限公司	
6~ $\leq 20 \pm 0.06$	DESIGN		Scale		NINGBO OUKERUI CONNECTOR CO., LTD.	
20~ $\leq 50 \pm 0.10$	CHECK		Sheet	1/1	PART NAME:	HZW-CKSF-35 (管母插针)
50~ $\leq 80 \pm 0.20$	APPROVE		Proj.		Drawing NO.	REV
					Material	A
						H62黄铜